

Uni-Body Foamer Complete With Gauges

MODEL: 975555-G

OVERVIEW

The Uni-Body Foamer With Gauges is a medium volume foam applicator for projecting foaming chemicals on to any surface up close or at a distance. This venturi injection system uses standard city water pressure (35 - 125 PSI) to draw and blend chemical concentrate into the water stream to create an accurately diluted solution. Rich, clinging foam is created by injecting compressed air into the solution to greatly increase volume and coverage ability. The foam is then projected through the discharge hose and fan nozzle at distances up to 12 feet. Gauges display incoming water and air pressure.

Key Features

- The unique machined polypropylene uni-body design is both compact and cost-effective
- Designed for foam cleaning medium to large surfaces
- Creates a medium volume of rich, clinging foam which increases chemical contact time and effectiveness
- Foaming expands the chemical and reduces over-application by providing visual assurance of coverage
- Fan pattern nozzle for fast coverage (up to 12' range)
- Covers up to 500 sq ft (46.5 sq m) in 2 minutes
- Adjustable foam consistency (wet/dry)
- Gauges display incoming water and air pressure to eliminate guessing
- Chemically resistant wetted components ensure years of outstanding performance with minimal maintenance
- Available without gauges (#975555)
- See other configurations of Lafferty city water pressure foamers in [Catalog 1](#)

Includes

- Machined polypropylene foamer body
- Incoming water and air pressure gauges
- 20 color-coded precision metering tips to set dilution ratios
- 40' discharge hose, stainless steel discharge ball valve, polypropylene foam wand and fan nozzle

Options

Large Stainless Steel Hose Rack	# 224150
Lid & Suction Hose for 1 & 5 Gallon Pails Pail Lid Suction Hose Assembly	# 709101
Stainless Steel Jug Racks	
Jug Rack, SS, 1 Gallon, Round/Square	# 224200
Jug Rack, SS, 2 1/2 Gallon	# 224210
Jug Rack, SS, 5 Gallon	# 224215
Alternate Check Valves - EPDM Standard	
Check Valve, Chemical, PP/Viton, 1/4"	# 491315
Check Valve, Air, SS/Viton, 1/4"	# 491306

APPLICATIONS

- Agriculture/Horticulture
- Animal Health
- Vehicle Wash
- Industrial
- Janitorial/Sanitation
- Metal Processing
- And Many Other Applications!



REQUIREMENTS

Chemical Concentrate

Water

Temperature	up to 160°F
Pressure	35 - 125 PSI
Flow	1.34 GPM @ 40 PSI
Supply Line	1/2"

Compressed Air

up to 3 CFM

Hose

3/4" x 40'

Nozzle

50250

Available from:



DEMA Australia
8/7-11 Parraweena Road
Caringbah NSW 2229

Ph: +61 2 9525 5177
Fx: +61 2 9525 5033
Eml: sales@demaust.com