



SPECIFICATIONS :

- > AIR OPERATED PUMP
- > MULTIPLE SEAL OPTIONS
- > PRESSURE REGULATOR INCLUDED
- > OPTIONAL CHEMICAL MIXING SYSTEMS AVAILABLE

ASPHALT RELEASE AGENT SPRAYER

Model Number: 900.TS5600V



The 900.TS5600V compressed air powered sprayer is the ideal method of applying asphalt & concrete release agents into tipper trays & concrete moulds. This systems uses a compressed air powered pump to pressurize the outgoing fluid line so that it's always ready for use. The pump automatically shuts down when the spray gun has been shut off. A pressure regulator is included & can be used to adjust the fluid pressure & flow rate. The pump has a maximum flow rate of 18 litres / minute at 90psi & uses only 2 - 3 cfm. The pump is available with Viton seals as standard & Santoprene or Kalrez on request. Unit is supplied with an outlet barb with 3/8" & 1/4" connections or a 3/8" compression or push fit connector on request.

For best results, use with a spray gun that has a long barrel to reduce the hazards of reaching over trays or moulds when applying the chemical.

DEMA AUSTRALIA

Unit 8, 7-11 Parraweena Road Caringbah NSW 2229

Phone: 61 (0)2 9525 5177 | Fax: 61 (0) 29525 5033 | www.dema.com.au