



Hone 400™

Honing Powder

DESCRIPTION

Aqua-Seal STC™ Hone 400™ is a safe, non acidic, easy to use honing powder designed to be used on calcium based stone eg: marble, limestone, travertine and cement based terrazzo. It will remove etch marks, light surface scratches, traffic wear patterns and produce an even flat non reflective honed finish.

USES

For calcium based stone eg: marble, limestone, travertine, cement based terrazzo where a smooth unpolished finish is desired.

TEST FIRST

Due to the nature of different surfaces, you should do several test areas in inconspicuous areas according to the label instructions to determine surface colour stability and desired results. The end user must determine the suitability of the product for their intended use.

PRECAUTIONS

1. Always Test first;
2. Read entire label and product technical bulletin before using;
3. Wear appropriate skin and eye protection;
4. Use when surface temperature is between 4°C and 32°C.

EQUIPMENT

1. Hogs hair or tan pads;
2. Weighted slow speed floor machine (175-300 RPM);
3. Clean water, wet vac, squeegee and broom;
4. Hone 400™.

INSTRUCTIONS

1. Surface must be free of all surface sealers and coatings;
2. Sweep, vacuum, or wipe surface;
3. Sprinkle Hone 400™ to the surface in a manageable area;
4. Add clean water to create a firm slurry;
5. Use a weighted slow speed floor machine (175-300 RPM) with 2 x hogs hair or tan pads double stacked and then start the honing process;
6. Do not allow product to dry - add water to the slurry as required;
7. Continue until the desired effect has been achieved;
Note: Use a squeegee to check your progress;
8. Remove the slurry with a wet vac and rinse thoroughly with clean water;
9. Repeat process as necessary;
10. Seal the surface with the appropriate Aqua-Seal STC™ sealer to provide stain resistance and ease the ongoing maintenance.

LIMITATIONS

- Do not mix with other chemicals or allow product to come in contact with any non-recommended surfaces;

COVERAGE

Approximately 25-40 square meters per 1kg. The coverage will vary depending on the surface density, hardness, porosity, texture, absorption, weather, the application method, severity of the problem and dilution used.

HANDLING AND STORAGE

- Close container tightly after each use.
- Store in original container only.
- Store in temperatures between 4°C and 32°C.

FIRST AID

For advice, contact a Poisons Information Centre (Phone 131 126) or a doctor. If swallowed, do NOT induce vomiting. Immediately give at least 3-4 glasses of water. If in eyes, hold eyelids apart and flush the eye continuously with running water. Continue flushing until advised to stop by the Poisons Information centre or a Doctor, or for at least 15 minutes. If skin or hair contact occurs, remove contaminated clothing and flush skin and hair with running water. If irritation persists, seek medical attention. In case of accident or if you feel unwell, seek medical advice immediately.

SAFETY DIRECTIONS

Avoid contact with skin and eyes.

WARRANTY

Aqua-Seal STC™ "The Manufacturer" warrants to the original purchaser of its products that such products are free from manufacturing defect and does not warrant or guarantee the workmanship performed by any person or firm installing its products. The manufacturer's obligation under this warranty is limited solely to the original purchaser and solely shall be limited to the replacement of the product sold. This warranty will not extend to any product which has been modified in any way or which has not been used in accordance with the printed instructions. The manufacturer makes no other warranties either expressed or implied. The end user must determine the suitability of the product for their intended use.

ALWAYS DO A TEST FIRST.

Stone
Restoration