



## Safe and Powerful Abrasive Cleaner

### DESCRIPTION

Aqua-Seal STC™ MicroScrub™ is safe yet powerful abrasive cleaner. Aqua-Seal STC™ MicroScrub™ is water based, biodegradable, No VOC, non toxic and non flammable. Does not contain any acids. No dwell time required. Will effectively remove most factory applied waxes and floor finishes, light grout residue (including epoxy), pencil marks, surface rust, mineral deposits, ground-in dirt and most sealer residues. Formulated to safely abrade away surface dirt and grime from heavily textured, hard to clean surfaces

### USES

Use on all natural stone, grout, ceramic, porcelain, terracotta, Saltillo, quarry tiles, terrazzo, concrete, pavers, masonry. Does not affect existing penetrating sealers. Aqua-Seal STC™ MicroScrub™ can also be used to boost the performance of any of cleaners or problem solvers.

### TEST FIRST

Due to the nature of different surfaces, you should do several test areas in inconspicuous areas according to the label instructions to determine surface colour stability and desired results. The end user must determine the suitability of the product for their intended use.

### PRECAUTIONS

1. Always Test first;
2. Read entire label and product technical bulletin before using;
3. Wear appropriate skin protection;
4. Use when surface temperature is between 4°C and 32°C.

### INSTRUCTIONS

1. Shake well before using;
2. Sweep, vacuum, or wipe surface;
3. Slightly pre wet surface;
4. Apply about ½ - 1 cup of Aqua-Seal STC™ MicroScrub™ to the pre wet surface;
5. Scrub the surface with a white nylon pad, scrub brush or scrub machine;
6. Remove the dirty solution with a wet vac or mop;
7. Rinse thoroughly with clean water;
8. Repeat the process as necessary.

### INSTRUCTIONS WHEN USED A BOOSTER

1. Shake well before using;
2. Sweep, vacuum, or wipe surface;
3. Dilute the selected cleaner or problem solver as per that products instruction label;
4. Carefully apply the solution to wet surface with a sponge or mop;
5. Allow selected cleaner or problem solver to dwell as per label instructions – DO NOT ALLOW THE PRODUCT TO DRY ON THE SURFACE;
6. Apply about ½ - 1 cup of Aqua-Seal STC™ MicroScrub™ to the standing solution;

7. Scrub the surface with a white nylon pad, scrub brush or scrub machine;
8. Remove the dirty solution with a wet vac or mop;
9. Rinse thoroughly with clean water;
10. Repeat the process as necessary.

### LIMITATIONS

- Do not allow product to come in contact with any non-recommended surfaces.

### COVERAGE

Approximately 30–300 square meters per 4 litres. The coverage will vary depending on density, porosity, texture, surface absorption, weather, time solution left on surface, the application method, severity of the problem and dilution used.

### HANDLING AND STORAGE

- Close container tightly after each use.
- Store in original container only.
- Store in temperatures between 4°C and 32°C.

### FIRST AID

For advice, contact a Poisons Information Centre (Phone 131 126) or a doctor. If swallowed, do NOT induce vomiting. Immediately give at least 3-4 glasses of water. If in eyes, hold eyelids apart and flush the eye continuously with running water. Continue flushing until advised to stop by the Poisons Information centre or a Doctor, or for at least 15 minutes. If skin or hair contact occurs, remove contaminated clothing and flush skin and hair with running water. If irritation persists, seek medical attention. In case of accident or if you feel unwell, seek medical advice immediately

### SAFETY DIRECTIONS

Avoid contact with skin and eyes.

### WARRANTY

Aqua-Seal STC™ "The Manufacturer" warrants to the original purchaser of its products that such products are free from manufacturing defect and does not warrant or guarantee the workmanship performed by any person or firm installing its products. The manufacturer's obligation under this warranty is limited solely to the original purchaser and solely shall be limited to the replacement of the product sold. This warranty will not extend to any product which has been modified in any way or which has not been used in accordance with the printed instructions. The manufacturer makes no other warranties either expressed or implied. The end user must determine the suitability of the product for their intended use.

ALWAYS DO A TEST FIRST.